


**NKCR7.E68961**  
**Auxiliary Devices Certified for Canada**

Page Bottom



**Auxiliary Devices Certified for Canada**

See General Information for Auxiliary Devices Certified for Canada

**IDEC CORP**

6-64 NISHIMIYAHARA 2-CHOME  
YODOGAWA-KU, OSAKA 532-0004 JAPAN

E68961

**Investigated to CAN/CSA-C22.2 No. 14**

**AS-interface fail-safe monitors** Model(s) SX5A-MBR01, SX5A-MBR02, SX5A-MBR03, SX5A-MBR04

**AS-interfaces** Model(s) FL1B-CAS2

**Auxiliary Device: Open type Pilot Lights** Model(s) AP22M, followed by 2 or 2T, followed by Q, followed by 3, 4, H, H2, M, M3 or M4, may be followed by any letters and/or numbers

**Contact blocks, "CW Series"** Model(s) CW-E01, CW-E10

**Contact blocks, open type** Model(s) HW-S01+, HW-S01R+, HW-S10+, HW-S10R+

**Control box enclosures, indoor use only, use with type 4X rated auxiliary devices** Model(s) FB Series

**Direct adapter LED pilot lights, "CW Series"** Model(s) CW-EAQ2, CW-EAQ3, CW-EAQ4, CW-EAQH, CW-EAQM, CW-EAQM4

**Direct Adaptor LED pilot lights, complete devices** Model(s) CW Series, followed by 1 or 4, followed by P, followed by 1 or 2, followed by E, followed by Q2, Q3, Q4, QH, QM or QM4.+

**Enabling switches, grip type** Model(s) HE1G, may be followed by -L, followed by 2, followed by 0, 1, 1S, 2, 2S or 11S; followed by M, may be followed by E, B, AB, L, AL or P, may be followed by B, N, 1Y, 1B or 1N, may be followed by Y, B, N, R or W, may be followed by Y, B, N, R or W.

**HW Series, contact blocks** Model(s) HW, followed by -C or -F, followed by B or L, followed by 0, 1, 2, 5, 6, 7, 8 or 9, followed by 0, 1, 2 or S, may be followed by -TKxxxx (internal tracking), for use with manufacturer's operator units and/or lamps.

**Illuminated display lights** Model(s) SLD, followed by 30, 44, 48 or 72, followed by manufacturer's control code, followed by 1, 2 or 3, followed by DH6, DH1, DH2, DW2, DHM1, DHM6, DHM2, TH1, TH2, TH12 or TH24, followed by B or N, followed by blank, S or T, followed by R, G, A, Y, W, S, PW or RG.

**Illuminated push-button switches, complete devices** Model(s) CW Series, followed by 1 or 4, followed by L, followed by M or A, followed by 1 or 2, followed by E, followed by 0, 1 or 2, followed by 0, 1 or 2, followed by Q2, Q3, Q4, QH, QM or QM4.+

**LED illuminated display lights, "LH Series"** Model(s) LH1D, followed by D2 or H2, may be followed by Z, M or N, followed by L, P or H, followed by Q4, followed by C05, C10, C20, C30 or C50, followed by R, A, W, Y, G, S, PW or ##, may be followed by W.+

LH1D, followed by D3, may be followed by Z, M or N, followed by L, P or H, followed by Q4, followed by C05, C10, C20, C30, C50, CN1 or CN2, followed by R, A, W, Y, G, S, PW or ###, may be followed by W.+

**Locking switches, enclosed type** Model(s) HS6E-, followed by A, B, C, D, L, M, N, P, DD, DM, DP, VA, VB, VC, VD, VL, VM, VN or VP, followed by 4 or 7Y, followed by 0 or 4, may be followed by B or R, maybe followed by 01 thru 99, maybe followed by R, G, A or Y.+

**N Series (panel cutout dimensions-30mm diam) illuminated push button switches** Model(s) ABLN, AL\*N, ALLN, ALN, ALNE, AOL\*N, AOLN, AOLNE, ULQN, UOLQN

**N Series (panel cutout dimensions-30mm diam) pilot lights** Model(s) APN, APNE, APNG, APNGE, UPQN, UPQNE

**N Series (panel cutout dimensions-30mm diam) push button switches** Model(s) AB, AO, AT, UB, UO, UT, UW or ABB, may be followed by Q, followed by N.

**N Series (panel cutout dimensions-30mm diam) selector push button switches** Model(s) ABN, may be followed by 6, 7 or 9, may be followed by L.