



Product Service

CERTIFICATE

No. B 15 04 13332 206

Holder of Certificate: IDEC CORPORATION2-6-64 Nishimiyahara, Yodogawa-Ku
Osaka
532-0004 JAPAN**Production Facility(ies):** 33644**Certification Mark:****Product:** Pushbutton switches
Electrical Emergency Stop Device**Model(s):** HA1B series
(See Attachment for nomenclature)**Parameters:**
Rated voltage: AC-15, AC-12(250Vac)
DC-13, DC-12(125Vdc)
Rated input current: AC-15(1.5A)
AC-12(3A)
DC-13(0.22A)
DC-12(0.4A)
Remark:
When installing/inserting the equipment all requirements
of the mentioned test standard must be fulfilled.**Tested according to:** EN 60947-5-5:1997/A11:2013

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: 73536629-02**Valid until:** 2020-04-08**Date,** 2015-04-13

(Shigehisa Ishikawa)

Page 1 of 2



B 15 04 13332 206

Nomenclature:

<u>HA</u>	<u>1</u>	<u>B</u>	-	<u>V</u>	<u>2</u>	<u>E</u>	<u>1</u>	<u>V</u>	<u>R</u>	-	<u>*****</u>
1	2	3		4	5	6	7	8	9		10

1. Series, HA
2. Bezel Shape
1 – Round
3. Non-illuminated / Illuminated type
B – Non-illuminated type
4. Function
V – Pushlock turn reset
5. Operator Shape
2 – Extended
4 – (40mm diam.) mushroom
6. Applicable Switch Unit
E – HA-E Series
7. Contact type
1 – 1 Normally closed contact
2 – 2 Normally closed contacts
8. Terminal Configuration
None – For Solder/tab
V – For PWB
9. Button color
R – Red
10. Manufacture's Control Number
***** - Additional letters and/or numbers