



IMPROVED CERTIFICATIONS SEARCH TOOL. REGISTER NOW!

[LEARN MORE](#)

QVAJ.E234997

Process Control Equipment for Use in Zone Classified Hazardous Locations

[Page Bottom](#)

Process Control Equipment for Use in Zone Classified Hazardous Locations

[See General Information for Process Control Equipment for Use in Zone Classified Hazardous Locations](#)

IDEC CORP

E234997

6-64 NISHIMIYAHARA 2-CHOME
YODOGAWA-KU, OSAKA 532-0004 JAPAN

[AEx ia] IIC, lamp barriers, "EB3L Series", Model(s) EB3L, followed by S, followed by 01, 02, 03, 05, 06, 08, 08C, 10, 16 or 16C, followed by S, followed by A or D, may be followed by C, intrinsically safe outputs for use in Class I, Zone 0, [AEx ia] Group IIC Hazardous Locations when installed in accordance with control drawing No. B-754-6.

[AEx ia] IIC, lamp barriers, "EB3L-N series", Model(s) EB3L, followed by S, followed by 01, 02, 03, 04C, 05, 06, 08, 08C, 10 or 16C, followed by K or S, followed by A or D, may be followed by -C, followed by N, intrinsically safe outputs for use in Class I, Division 1, Groups A, B, C and D, Class II, Division 1, Groups E, F, G and Class III, Division 1; or Class I, Zone 0, Group IIC Hazardous Locations when installed in accordance with control drawing No. B-1341-7.

[AEx ia] IIC, relay barriers, "EB3C Series", Model(s) EB3C, followed by R or T, followed by 01, 02, 03, 05, 06, 08, 08C, 10, 16 or 16C, followed by S, followed by A or D, may be followed by C, intrinsically safe outputs for use in Class I, Zone 0, [AEx ia] Group IIC Hazardous Locations when installed in accordance with control drawing No. B-578-6.

[AEx ia] IIC, relay barriers, "EB3C-N Series", Model(s) EB3C, followed by R, T or M, followed by 01, 02, 03, 04C, 05, 06, 08, 08C, 10 or 16C, may be followed by K or S, followed by A or D, may be followed by -C, followed by N, intrinsically safe outputs for use in Class I, Division 1, Groups A, B, C and D, Class II, Division 1, Groups E, F, G and Class III, Division 1 or Class I, Zone 0, Group IIC Hazardous Locations when installed in accordance with control drawing No. B-1340-7.

[AEx ia] IIC, relay barriers, "EB3N Series", Model(s) EB3N-A2ND (a), EB3N-A2R5D (a), EB3N-A2T5KD (a), EB3N-A2T5SD (a), EB3N-M2ND (a), EB3N-M2R5D (a), EB3N-M2T5KD (a), EB3N-M2T5SD (a)

(a) - Intrinsically safe outputs for use in Class I, Division 1, Groups A, B, C and D, Class II, Division 1, Groups E, F, G and Class III, Division 1; or Class I, Zone 0, Group IIC, Hazardous Locations when installed in accordance with control drawing number B-1156-4.



Trademark and/or Tradename:

IDEC

[Last Updated](#) on 2017-05-16

[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".